

The Leader in Fuel Cleaning & Maintenance Systems



Fuel Solutions

Las Vegas



The **Enviro 3** is designed to keep middle distillate fuel in main storage tanks under 8,000 gallons in a pristine state.

ENVIRO 3

Up To
8,000 Gal Tanks
Micro-Processor Based
Time Switch

The **Enviro 3** is a wall mounted, close looped system with leak detection and built-in diagnostics that give you healthy fuel to run your equipment and a clean storage tank at the same time.

Fully automated UL listed control panel with a microprocessor based time switch for ease of use and maintenance. This system monitors fuel contamination levels and alerts the user of saturation levels and maintenance needs on an LED display. For your convenience, alarms can also be interfaced with central plant monitoring. Maintenance can then be scheduled and the system brought back on line.

This system was also designed to meet environmental issues for safe operation and offers complete fuel remediation and control. Detailed written specifications are available upon request.

Weight: 220 lbs.

Size: 38" h x 30" w x 10" d

Power: 120 VAC/6.8A 50/60HZ single phase

Plumbing: 3/4" black pipe or larger depending on length of run

Flow Rate: 8gpm = 480gph

Multiple Stages of Filtration:

Stage 1: 150 micron particulate and bulk water removal through a cartridge type strainer and water separator.

Stage 2: 2 micron particulate and 99.995% emulsified water removal through a spin-on canister type element.

Not For Use With Gasoline